



TeraStation™ 3010 Series

TS3210DN, TS3410DN, TS3410RN



GET SERIOUS ABOUT PROTECTING YOUR DATA

The Buffalo TeraStation 3010 NAS series is designed for small businesses that want to take the next step in protecting their valuable business data. No more backing up to thumb drives or disks that get misplaced – it's time to get serious about data.

Designed for organizations around 25 users, the TS3010 series delivers the same features and functionality as more advanced NAS solutions from Buffalo. With the TS3010, small businesses can take advantage of the reliability and security typically reserved for enterprise level organizations.

Instead of backing up to thumb drives and managing multiple tape or external hard drives, TeraStation 3010 can automate your backup plan including local and cloud-based strategies. Automation saves you time, money and ensures better results should you need to recover data. Optional data encryption as well as Buffalo's integrated software ensures hard drive data cannot be accessed on systems other than your TeraStation. Physical security is addressed with an integrated Kensington security slot, drive bay panel lock and Buffalo's Boot Authentication software.

The out-of-box experience is simplified as TeraStation 3010 ships fully populated with NAS-quality hard drives preconfigured in RAID. Designed for reliable operations in an always-on environment, NAS drives are much more stable and reliable than standard desktop hard drives. RAID protects your data by storing bits and bytes across multiple hard drives instead of a single drive. If a drive is lost, systems stay up allowing you to continue to work while the replacement is sent from Buffalo.

Product Highlights:

- Available in 2-bay and 4-bay desktop models and a 1U 4-bay rackmount model
- 1.4GHz Annapurna dual-core processor and 1 GB DDR3 RAM
- NAS-grade hard drives designed for reliability in always-on operation
- Storage capacity from 4 TB up to 16 TB
- Buffalo's unique Boot Authentication feature ensures the device is only accessible on authorized networks
- Data & drive encryption securing your data
- Integrated backup to 3rd party cloud services and private cloud support for advanced protection
- Supported by Windows, Windows Server and Mac OS
- Includes NovaBACKUP® Buffalo Edition software with one server and ten workstation licenses
- Remote access via free WebAccess service
- Three-year limited warranty with additional warranty services available
- 24/7 US-based technical support



AT BUFFALO, WE'RE ALWAYS ON

We're working hard at Buffalo to make technology painless for customers. That starts with designing products that are reliable and easy to deploy. Our 24/7 US-based support experts can help de-mystify technology and select the solutions that are right for your business. We're also available to resolve questions that may come up during installation or once the solution has been implemented. Our goal is to make things easier for you and to help you be successful – give us a call!

SMB SOLUTION: UP TO 25 USERS

MODELS Part Numbers	TS3210DN (2-BAY) TS3210DN0402 TS3210DN0802	TS3410DN (4-BAY) TS3410DN0404 TS3410DN0804 TS3410DN1204 TS3410DN1604	TS3410RN (4-BAY RACKMOUNT) TS3410RN0404 TS3410RN0804 TS3410RN1204 TS3410RN1604
Configuration	Desktop	Desktop	Rackmount
INTERNAL HARD DRIVES			
Number of Drives	2	4	4
Capacity Range	4, 8 TB	4, 8, 12, 16 TB	4, 8, 12, 16 TB
Drive Interface	SATA 6 Gbps	SATA 6 Gbps	SATA 6 Gbps
Supported RAID	0/1/ JBOD (Individual Disks)	0/1/5/6/10/ JBOD (Individual Disks)	0/1/5/6/10/ JBOD (Individual Disks)
USB INTERFACE			
Standards Compliance	USB 3.0	USB 3.0	USB 3.0
Connector Type	A type	A type	A type
Number of Ports	2x USB 3.0	2x USB 3.0	3x USB 3.0
Data Transfer Rates	5 Gbps	5 Gbps	5 Gbps
PERFORMANCE			
CPU	Annapurna Labs® Alpine Processor AL212 (1.4 GHz Dual-Core)	Annapurna Labs® Alpine Processor AL212 (1.4 GHz Dual-Core)	Annapurna Labs® Alpine Processor AL212 (1.4 GHz Dual-Core)
Memory	1 GB DDR3	1 GB DDR3	1 GB DDR3
ENVIRONMENTAL & POWER			
Power Consumption	Max 85W	Max 85W	Max 100W
Power Supply	Internal AC 100-240V Universal 50/60Hz	Internal AC 100-240V Universal 50/60Hz	Internal AC 100-240V Universal 50/60Hz
Operating Temperature	32° - 104°F (0° - 40°C)	32° - 104°F (0° - 40°C)	32° - 104°F (0° - 40°C)
Operating Humidity	10 - 85% non-condensing	10 - 85% non-condensing	10 - 85% non-condensing
SHIPPING			
Package Dimensions (LxWxH)	14.09 x 12.24 x 12.60 in	14.06 x 12.18 x 14.31 in	23.03 x 21.26 x 7.87 in
Package Weight	11.24 lbs	16.09 lbs	19.84 lbs
LAN INTERFACE	IEEE802.3ab (1000BASE-T), IEEE802.3u (100BASE-TX), IEEE802.3 (10BASE-T)		
Number of Ports	2 (1000BASE-T)		
Data Transfer Rates	1000 Mbps / 100 Mbps / 10 Mbps		
Supported Protocols	TCP/IP		
Network File Services	CIFS/SMB, AFP, FTP/FTPS/SFTP, NFS		
Connector Type	RJ-45		
CLIENT OS SUPPORT	Windows® 10, Windows® 8.1 (32-bit/64-bit), Windows® 7 (32-bit/64-bit), Windows Server® 2016, Windows Server® 2012, Windows Server® 2008, Windows Server® 2008R2, Mac® OS® X 10.9 or later		
ACCESSORIES			
Compatible Hard Drives	OP-HD1.0N, OP-HD2.0N, OP-HD4.0N, OP-HD6.0N		
Warranties	3YNBD20, 3YKYD40, 3YKYD30, 3YKYD20, 5YNBD40, 5YNBD30, 5YNBD20, 5YKYD40, 5YKYD30, 5YKYD20		
BOX CONTENTS	TeraStation™, Quick Setup Guide, 6a Ethernet Cable, Rail Kit with Mounting Brackets and Screws*, AC Cable, Front Panel Key**, and Warranty Statement * TS3410RN only **TS3210DN & TS3410DN only		

TeraStation™ 3010 Series

